DT66

Enterprise Mobile Computer

- 6.5-inch ultra-high-definition (720*1600) thin-bezel display, offers more information at one page and less scrolling.
- Supports in-display and backside NFC reading to meet diverse usage needs.
- The 5000mAh smart battery with a built-in battery management system enhancing overall battery life. With the hot swap feature, it achieves uninterrupted 24-hour operation.
- Powered by the latest Qualcomm 2.4GHz high-performance processor, it delivers exceptional processing speed, further empowering faster decoding of 1D/2D/DPM barcode.
- Wi-Fi 6E and 5G delivers the super fast and reliable wireless connections.
- Optional iToF camera for three-dimensional volume measurement of parcel.





2.4GHz Processor



Android 13 O.S.



IP68 Sealing



6.5-inch Display



5000mAh Smart Battery





Trigger



4-Slot Battery Charging Cradle



Charging Cradle

DT66 Enterprise Mobile Computer Specifications





Octa-core 2.4 GHz



Android 13, upgradable to Android 18 Support GMS/AER



RAM: 4GB ROM: 64GB RAM: 8GB ROM: 128GB (optional) Micro SD Card, Up to 256 GB



6.5 inch display, 720*1600



Touch Screen

Ultra sensitive capacitive touch panel, support multi-touch, works with gloves and wet fingers

Dimensions

175.8 mm L x 76.5 mm W x 14.5 mm D Weight: About 283g ⊖ Scanning

Professional scan engine Support international standard 1D/2D barcode; Support barcode displayed on screen



Front: 5MP FF; Rear: 13MP PDAF Optional iToF camera ⟨o⟩ Sensors

Light + Accelerator+ Proximity + Geomagnetic + Gyro+ Pressure(optional)



Dual-Microphone with noise cancellation, 1.5W speaker for loud noise, reciever supports echo cancellation



Capacity: 3.85V 5000mAh Support hot swap

Buttons

PWR button Vol +/- button Scan button*2 Custom button



Nano- SIM x 2, Micro SD Slot x 1, (Reserved support eSIM) Communication

5G/4G/3G/2G Bluetooth: BT5.2 + BR/EDR + BLE Wi-Fi: Wi-Fi 6E, 2.4G/5G Support 2x2 MU-MIMO, IEEE 802,11a/b/g/n/ac/d/e/h/i/k/r/v/w/ax

Roaming: 802.11r (Over the Air);OKC/;PMKID caching

GPS BEIDOU GLONASS Galileo

Positioning

Protection

IP68 dustproof and waterproof 1.5-meter drop resistance

Environmental

Operating Temp.: -20 ~ +60°C Storage Temp.: -40 ~ +70°C Humidity: 5%RH ~ 95%RH(No condensation) ESD: +/-15kv Air; +/-8kv contact

UROVO PTE. LIMITED

Website: en.urovo.com Email: urovo@urovo.com

Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1,

Singapore 048616

*This page is subject to change without prior notice